

IP CAMERA

HS-D070SQ-H

- H.265 / H.264 / MJPEG
- 2MP (1920 × 1080)
- 30 ~ 50 M IR night view distance
- 3 DNR, Digital WDR, HLC, BLC, Digital Defog
- 1CH built-in MIC; Hardware reset
- Built-in micro SD card slot, up to 128GB
- ICR auto switch, true day / night
- Support ROI coding
- IP67 ingress protection
- Support DC 12V / PoE power supply
- Intelligent analytics: Video blur detection, Line Crossing, Intrusion








RoHS **CE** **FC**





HS-D070SQ-H

Camera	
Image Sensor	1 / 2.9 " CMOS
Image Size	1920 × 1080
Electronic Shutter	1 / 25 s ~ 1 / 100000 s
Min. Illumination	0.0035 lux@F1.2,AGC ON; 0 lux with IR 0.013 lux@F2.0,AGC ON; 0 lux with IR
Lens	VF 2.8 ~ 12 mm @F1.4
Horizontal view Angle	88° ~34.8°
IR Distance	30~50 m
Day & Night	ICR auto switch
WDR	YES
BLC	YES
HLC	YES
Digital Defog	YES
Digital DNR	3 DNR
Image	
Video Compression	H.265 / H.264 / MJPEG
H.265 Compression Standard	Main Profile @Leve4.1 High Tier
Resolution	1080P (1920 × 1080), 720P (1280 × 720), D1, CIF, 480 × 240
Main Stream (S1)	1080P / 720P @30fps
Sub Stream (S2)	D1 / CIF / 480 × 240 @30fps
Third Stream (S3)	-
Bit Rate	64 Kbps ~ 6 Mbps
Bit Rate Type	VBR / CBR
Image Settings	ROI, Saturation, Brightness, Chroma, Contrast,Wide Dynamic, Sharpen,NR,etc. adjustable through client software or web browser
ROI	Each ROI to be configured separately
Audio	
Audio Compression	G.711A / U
Two-way audio	-
Interfaces	
Network	1 x RJ45
Video Output	-
Audio	1CH built-in MIC
Storage	
SD card	Built-in micro SD card slot; up to 128GB
Network remote storage	Yes
Hardware Reset	Yes

Functions			
Remote Monitoring	Web browsing,CMS remote control		
Online Connection	Support simultaneous monitoring for up to 3 users Support multi-stream real time transmission		
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, 802.1x, UPnP, HTTPS, HTTP, QoS		
Interface Protocol	ONVIF		
Smart Alarm	Motion detection, SD card full, SD card error		
Intelligent Analytics	Video blur detection, Line Crossing, Intrusion		
General function	Watermark, IP address filtering, video mask, heartbeat, illegal login lock		
PoE	Yes , IEEE802.3 af		
Others			
Power Supply	DC12V / PoE		
Power Consumption	< 8W		
Operating Environment	- 30 ° C ~ 60 ° C (-22° F~140° F) Humidity: less than 95 % (non-condensing)		
Dimensions	Φ 111.5 × 99.6		
Weight	Approx. 640g		
Installation	Ceiling mounting (wall mounting available with the junction box and bracket)		
Ingress Protection	IP67		
Accessories			
			
B624TV	B637	B609	
			
B615	B616	B626	B625