

H.265 NVR Plug & Play

32CH/64CH H.265/H.264 NVR HS-NB3380/HS-NBA380



- Plug & Play supported.
- Multi stream supported.
- Mobile remote surveillance. (iPhone/ iPad/ Android)
- 2 way audio. (conference)
- Recording retention function supported.
- USB or remote firmware upgrade supported.
- Network online user management.
- Digital zoom on live and playback.
- Recorded file protection supported.
- Intensive security function by authority.
- Directly AVI format backup.
- Firefox and IE browser supported. (Windows)
- Safari browser supported on MAC OS.
- Support 16 CH playback.
- Multi-user online simultaneously.
- ONVIF V2.4 (Profile S).

Specifications

Model	HS-NB3380	HS-NBA380
Channel	32CH	64CH
Compression Method	H.265 / H.264	
Video Output	VGA	1920x1080 / 1280x1024
	HDMI 1	4K : 3840x2160 / 1920x1080 / 1280x1024
	HDMI 2	1920x1080 / 1280x1024
Color	16.7 million	
Bit Rate	1Mbps ~ 10Mbps	
Stream transmission	CBR / VBR	
Display Channel	1 / 4 / 9 / 16 / 25 / 32	
Sequence Display	Available	
Recording Resolution	8M/5M/4M/3M/1080P/960P/720P@960fps	8M/5M/4M/3M/1080P/960P/720P@1920fps
Record Quality	Highest / Higher / High / Medium / Lower / Lowest	
Recording Mode	Motion / Manual / Schedule	
Playback Mode	Date & Time search / Event search	
Multi-task	Live / Record / Play / Network / Backup	
Backup	USB 3.0x1 / USB 2.0x2 / Network remote backup	
Storage	SATA x8 (10TB each)	
Audio	Input : 1 ; Output : 1	
Alarm	Input : 8 ; Output : 4	
Load Bandwidth (Mbps)	256	320
HDD Record Mode	Full stop / overwrite	
Mobile Surveillance	iPhone / iPad / Android	
RS485	Yes	
IR Remote controller	Standard	
Mouse	Standard	
Ethernet	RJ45 x2 (10/100/1000 M Base-T)	
Network-Function	Support licensed CMS(100CH) / EMAP / IE	
Network Connection	TCP/IP, PPPoE, DHCP, DDNS(Auto DDNS)	
Client Application	Display / Playback / Backup / DVR control / PTZ Control	
Power Source	AC 110V / 230V	
Operating Temperature	5°C ~ 40°C	
Operating Humidity	Less than 90%	
Dimension	430(W) x 89(H) x 450(D) mm	

Dimension Unit : mm

